

Model: TYA9467EKS
Product Description

Type: Reciprocating
Application: CBP - Commercial Back Pressure
Refrigerant: R-22
Voltage/Frequency: 220-240V ~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	220V ~ 50HZ	9800	2470	2872	1270	7.72	1.94	2.26	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range: N/A
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 19
Weight Unit of Measure: KG
Displacement (cc): 22.3
Oil Type: N/A
Viscosity (cSt): N/A
Oil Charge (cc): 0

Electrical

Voltage Range (50 Hz): 198-264
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 31
Rated Load Amps (RLA 50 Hz): 5.3
Rated Load Amps (RLA 60 Hz): 0
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: N/A
Motor Resistance (Ohm) - Start: N/A
Motor Type: CSR
Overload Type: N/A
Relay Type: N/A

Agency Approval

IRAM Listed