

Model: AE4430E-FZ1A
Product Description

Type: Reciprocating
Application: HBP/CBP - High/Commercial
 Back Pressure
Refrigerant: R-22
Voltage/Frequency: 220-240V ~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	220V ~ 50HZ	2650	668	777	318	8.33	2.1	2.44	-23°C (-10°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 0
Weight Unit of Measure: N/A
Displacement (cc): 5.16
Oil Type: Synthetic Alkylate
Viscosity (cSt): 32
Oil Charge (cc): 380

Electrical

Voltage Range (50 Hz): 198-253
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 14.5
Rated Load Amps (RLA 50 Hz): 1.97
Rated Load Amps (RLA 60 Hz): 0
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 9.392
Motor Resistance (Ohm) - Start: 12.024
Motor Type: CSIR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, VDE Listed



Tecumseh

Performance Data Sheet

AE4430E-FZ1A

General Information

Model	AE4430E-FZ1A	Refrigerant	R-22
Test Condition	EN12900	Performance Test Voltage	220V ~ 50HZ
Return Gas	20°C (68°F) RETURN GAS	Motor Type	CSIR

Performance Information

Evap Temp (°C)	Condensing Temperature (°C)				
		30	40	50	60
-15	Btu/h	1330	1160	984	794
	Watts (Power)	190	206	218	228
	Amps	1.60	1.63	1.66	1.68
	Lb/h	16.7	15.6	14.3	12.7
-10	Btu/h	1680	1480	1270	1050
	Watts (Power)	200	221	239	254
	Amps	1.62	1.67	1.72	1.76
	Lb/h	21.2	19.9	18.6	16.9
-6.7	Btu/h	1950	1710	1480	1240
	Watts (Power)	205	230	251	271
	Amps	1.63	1.69	1.75	1.81
	Lb/h	24.5	23.2	21.7	20.1
-5	Btu/h	2090	1850	1600	1340
	Watts (Power)	207	234	257	279
	Amps	1.64	1.71	1.77	1.84
	Lb/h	26.4	25.0	23.5	21.8
0	Btu/h	2570	2270	1970	1670
	Watts (Power)	210	243	273	302
	Amps	1.65	1.74	1.82	1.91
	Lb/h	32.7	31.0	29.3	27.4
5	Btu/h	3120	2760	2400	2050
	Watts (Power)	209	249	287	323
	Amps	1.65	1.76	1.87	1.99
	Lb/h	40.1	38.0	36.0	33.9
7.2	Btu/h	3390	2990	2610	2230
	Watts (Power)	207	250	291	331
	Amps	1.65	1.76	1.89	2.02
	Lb/h	43.7	41.5	39.3	37.1
10	Btu/h	3750	3310	2890	2470
	Watts (Power)	203	251	296	340
	Amps	1.64	1.77	1.91	2.05
	Lb/h	48.7	46.3	43.9	41.5

15	Btu/h	4460	3940	3440	2950
	Watts (Power)	190	247	300	353
	Amps	1.61	1.76	1.93	2.11
	Lb/h	58.7	55.8	53.0	50.2

COEFFICIENTS	CAPACITY	POWER	CURRENT	MASS FLOW
C1	3.547571E+03	7.199414E+01	1.444132E+00	3.828367E+01
C2	1.416169E+02	-3.434053E+00	-6.367075E-03	1.612174E+00
C3	-3.533689E+01	5.930967E+00	5.411817E-03	-2.179577E-01
C4	2.027131E+00	-1.261557E-01	-3.604921E-04	2.697507E-02
C5	-1.422353E+00	1.146183E-01	1.512396E-04	-1.021015E-02
C6	1.159371E-01	-5.344898E-02	6.054290E-05	1.491825E-03
C7	8.479343E-03	-1.039575E-03	-3.869389E-06	1.913689E-04
C8	-1.901888E-02	1.272095E-03	4.618710E-06	-1.522497E-04
C9	3.801180E-03	2.662802E-04	3.483471E-06	5.770488E-05
C10	-7.987408E-04	3.079898E-04	-3.390806E-07	-1.468537E-05

$$\text{Value} = C1 + C2 * Te + C4 * Te^2 + C7 * Te^3 + (C3 + C5 * Te + C8 * Te^2) * Tc + (C6 + C9 * Te) * Tc^2 + C10 * Tc^3$$

Te = Evaporator Temperature

Tc = Condensing Temperature



Tecumseh

Performance Data Sheet

AE4430E-FZ1A

General Information

Model	AE4430E-FZ1A	Refrigerant	R-22
Test Condition	EN12900	Performance Test Voltage	220V ~ 50HZ
Return Gas	20°C (68°F) RETURN GAS	Motor Type	CSIR

Performance Information

Evap Temp (°F)		Condensing Temperature (°F)						
		80	90	100	110	120	130	140
5	Btu/h	1390	1300	1200	1100	1000	901	794
	Watts	184	194	203	211	217	223	228
	Amps	1.58	1.60	1.62	1.64	1.66	1.67	1.68
	Lb/h	17.0	16.5	15.9	15.2	14.5	13.6	12.7
10	Btu/h	1580	1480	1370	1270	1160	1050	934
	Watts	188	201	211	220	228	236	243
	Amps	1.59	1.62	1.64	1.67	1.69	1.71	1.72
	Lb/h	19.4	18.8	18.2	17.5	16.8	15.9	15.0
15	Btu/h	1800	1680	1560	1450	1330	1210	1080
	Watts	192	206	218	229	239	248	257
	Amps	1.61	1.63	1.66	1.69	1.72	1.74	1.77
	Lb/h	22.1	21.4	20.8	20.0	19.2	18.4	17.4
20	Btu/h	2030	1900	1770	1640	1510	1380	1240
	Watts	195	211	225	237	249	260	271
	Amps	1.61	1.65	1.68	1.71	1.75	1.78	1.81
	Lb/h	25.0	24.3	23.5	22.8	21.9	21.1	20.1
25	Btu/h	2280	2140	1990	1850	1700	1560	1410
	Watts	197	215	230	245	258	271	284
	Amps	1.62	1.66	1.70	1.74	1.78	1.81	1.85
	Lb/h	28.2	27.4	26.6	25.8	24.9	24.0	23.0
30	Btu/h	2560	2390	2230	2070	1910	1760	1600
	Watts	198	217	235	251	267	282	297
	Amps	1.62	1.67	1.71	1.76	1.80	1.85	1.90
	Lb/h	31.7	30.9	30.0	29.0	28.1	27.1	26.1
35	Btu/h	2850	2670	2490	2320	2140	1970	1790
	Watts	197	219	238	257	275	292	309
	Amps	1.62	1.67	1.72	1.78	1.83	1.88	1.94
	Lb/h	35.6	34.6	33.6	32.6	31.6	30.6	29.5
40	Btu/h	3180	2970	2780	2580	2390	2190	2000
	Watts	195	219	240	261	281	301	320
	Amps	1.62	1.67	1.73	1.79	1.85	1.92	1.98
	Lb/h	39.9	38.7	37.6	36.5	35.4	34.3	33.1

45	Btu/h	3520	3300	3080	2860	2650	2440	2230
	Watts	191	217	241	264	287	309	331
	Amps	1.61	1.67	1.74	1.80	1.87	1.94	2.02
	Lb/h	44.5	43.2	42.0	40.8	39.6	38.4	37.1
50	Btu/h	3900	3650	3410	3170	2930	2700	2470
	Watts	186	214	240	266	291	315	340
	Amps	1.60	1.67	1.74	1.81	1.89	1.97	2.05
	Lb/h	49.5	48.1	46.8	45.5	44.1	42.8	41.5
55	Btu/h	4300	4030	3760	3500	3240	2980	2730
	Watts	178	209	238	266	293	321	348
	Amps	1.58	1.65	1.73	1.82	1.90	1.99	2.09
	Lb/h	55.0	53.5	52.0	50.5	49.0	47.6	46.1
60	Btu/h	4730	4430	4140	3850	3560	3280	3010
	Watts	169	202	233	264	294	324	354
	Amps	1.56	1.64	1.72	1.82	1.91	2.01	2.12
	Lb/h	61.0	59.3	57.6	56.0	54.4	52.8	51.2

COEFFICIENTS	CAPACITY	POWER	CURRENT	MASS FLOW
C1	1.928278E+03	2.532570E+00	1.392237E+00	1.880613E+01
C2	5.113703E+01	-6.019999E-01	2.285218E-03	5.211228E-01
C3	-1.029907E+01	3.697832E+00	2.172564E-03	-6.391877E-02
C4	5.904360E-01	-2.880453E-02	-7.291206E-05	6.010923E-03
C5	-2.719998E-01	1.849397E-02	-4.223392E-05	-2.113752E-03
C6	2.807410E-02	-2.302746E-02	5.153963E-06	3.855495E-04
C7	1.453934E-03	-1.782536E-04	-6.634754E-07	3.281360E-05
C8	-3.261124E-03	2.181233E-04	7.919599E-07	-2.610591E-05
C9	6.517798E-04	4.565847E-05	5.973029E-07	9.894527E-06
C10	-1.369583E-04	5.281033E-05	-5.814140E-08	-2.518068E-06

$$\text{Value} = C1 + C2 * Te + C4 * Te^2 + C7 * Te^3 + (C3 + C5 * Te + C8 * Te^2) * Tc + (C6 + C9 * Te) * Tc^2 + C10 * Tc^3$$

Te = Evaporator Temperature

Tc = Condensing Temperature